

## GLOBAL EQUIPMENT AND MACHINERY SALES, INC

345 HORSHAM ROAD, HORSHAM, PA 19044

TEL: +1.215.674.3500 \* FAX: +1.215.674.3340

**Web:** [www.globalequip.com](http://www.globalequip.com) **E-Mail:** [info@globalequip.com](mailto:info@globalequip.com)

### Liquidation of Deink Facility-Remaining Items

**Must be Sold Immediately!!**

Lamort/Fiberprep 16' diameter stainless steel high consistency Helico pulper. Solid stainless steel tub and rotor. 14' tub height. 35 cubic meter (9200 gallon) tub volume. Driven by an 800 HP motor through a Faulk gearbox. Capable of pulping at up to 15% consistency.



**Global Is Always Looking for Good Surplus Machinery. Click [info@globalequip.com](mailto:info@globalequip.com) If You Have Any Machinery For Sale**

**Contact Global For More Information and Pricing**

## GLOBAL EQUIPMENT AND MACHINERY SALES, INC

345 HORSHAM ROAD, HORSHAM, PA 19044

TEL: +1.215.674.3500 \* FAX: +1.215.674.3340

**Web: [www.globalequip.com](http://www.globalequip.com) E-Mail: [info@globalequip.com](mailto:info@globalequip.com)**

Lamort/Fiberprep Size IV batch Scavenger (Poire). All stainless steel construction. Belt driven by a 200 HP motor. Last used in a 200 TPD deinking line in conjunction with a 16' diameter Lamort/Fiberprep hi-consistency Helico pulper. This machine is in very good condition. Also suitable in OCC, double lined kraft, and virgin pulp applications. Use of Lamort batch Scavengers reduces downstream equipment requirements.



**Global Is Always Looking for Good Surplus Machinery. Click [info@globalequip.com](mailto:info@globalequip.com) If You Have Any Machinery For Sale**

**Contact Global For More Information and Pricing**

## GLOBAL EQUIPMENT AND MACHINERY SALES, INC

345 HORSHAM ROAD, HORSHAM, PA 19044

TEL: +1.215.674.3500 \* FAX: +1.215.674.3340

**Web:** [www.globalequip.com](http://www.globalequip.com) **E-Mail:** [info@globalequip.com](mailto:info@globalequip.com)

(2) Lamort/Fiberprep model GYT5 Gyrocleans. Previously driven by a 75 HP motor. T316L stainless steel contacts. Rotating cylindrical body. Removes small, lightweight contaminants at up to 2% consistency. Double mechanical seals on each end. 60PSI. Process output for GYT5 ranges from 1,940 to 2,290 GPM (440 - 520 m<sup>3</sup>/hr) depending on the specific application. Suitable for a variety of applications, including deink, OCC, mixed waste, and virgin pulps, as well as approach flow systems.



**Contact Global For More Information and Pricing**

**Global Is Always Looking for Good Surplus Machinery. Click [info@globalequip.com](mailto:info@globalequip.com) If You Have Any Machinery For Sale.**